



MOBIROOF ECO



MobiRoof ECO is a ready-made green roof system that consists of a plant cassette filled with substrate and available with two selections of plants. The cassettes are easily placed against each other, creating a green roof immediately. MobiRoof ECO is an extensive green roof system suitable for flat roofs and roofs with a slope angle of up to 10 degrees (20%) and always remains movable. MobiRoof ECO is a circular green roof system. The cassette is made of recycled material and fully recyclable. This reduces environmental pressure and reduces waste flow. The cassettes are pre-grown locally with cuttings from our own nursery.

BENEFITS

- Collection and buffering of rainwater
- Stimulates biodiversity
- Insulating and sound-absorbing effect
- Extends the life of the roof
- Aesthetic value
- Increases the value of real estate.
- Increased efficiency of solar panels
- Eligible for subsidies and tax breaks

FEATURES

- Ready-to-use cassette viable with two selections of plants
- Lightweight green roof system
- Ready for use as roof cover
- Easy to install and replace
- Water retention of 20 litres per m² (optional 40 litre per m²)
- Sustainably and locally produced.
- Circular, recycled and fully recyclable
- Low maintenance
- Can be used on both flat and slightly sloping roofs

bicycle parking car parks new construction
roofs renovation garden houses bus stops

TECHNICAL INFORMATION

CASSETTE MATERIAL

The cassette is made of regenerated non-toxic polypropylene (PP) produced in the Netherlands.

DIMENSIONS

The external measurements of the cassettes are 50 x 50 x 6 cm (=0.25 m²). 4 cassettes therefore fit into 1 m².

WATER RETENTION

The cassette is filled with a substrate which, in addition to the function of growth medium, ensures drainage and storage of water. The water capacity is approximately 20 litres per m². As a result, the MobiRoof ECO green roof system is eligible for subsidies and tax advantages. The water buffer capacity can be increased by adding a buffer layer under the cassette (optional 40 litre per m²).

VEGETATION

MobiRoof ECO is available with two selections of plants. MobiRoof ECO - Sedum is provided with 6 to 8 different types of sedums, while MobiRoof ECO - Sedum & Wildflower is provided with the same sedum and a wildflower mix comprised of a variety of flowers, flowering herbs and ornamental grasses (20 to 24 species).

WEIGHT

MobiRoof ECO weighs approximately 38 kg per m² when dry and approximately 58 kg per m² when completely saturated with water.

FINISH

Gravel can be added around outer roof edges, roof windows, skylights and drainage piping for example, to stimulate the micro-climate and prevent wind reaching under the cassettes.

ROOF PITCH

The MobiRoof ECO system can be applied to flat roofs and those with a slight angle of up to 10 degrees (20%). MobiRoof ECO can be installed as is, with no further action required.

ROOF PROTECTION

Apply root-resistant permeable sheeting on the roof before installing the cassettes when the roofing does not include a root-resistant layer.

IRRIGATION

Under extreme drought conditions irrigation is recommended.

MAINTENANCE

Maintenance work is required once or twice a year. The maintenance tasks are as follows:

- General checks
- Watering
- Pruning
- Fertilizing